NSN 5315-00-275-4990

Threaded Tapered Pin - Page 1 of 2

First End Style:



View Online at https://aerobasegroup.com/nsn/5315-00-275-4990

| Chamfered |
|--|
| Second End Style: |
| Oval |
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.594 inches |
| Taper Length: |
| 5.688 inches |
| Taper Minor Diameter: |
| Between 0.603 inches and 0.607 inches |
| Taper Major Diameter: |
| 0.8439 inches |
| First End Taper Length: |
| Any acceptable |
| Grip Length: |
| 5.500 inches |
| Second End Relationship With First End: |
| Not identical |
| Hardness Rating: |
| 27.0 rockwell c and 32.0 rockwell c |
| Thread Size: |
| 0.500 inches |
| Taper: |
| 0.500 per foot in inches |
| First End Location: |
| Threaded end |
| First End Taper Angle: |
| 45.0 degrees |
| Second End Outer Radius: |
| Any acceptable |
| Material: |
| Steel comp 4130 or steel comp 8630 |
| Material Specification: |
| Astm a-322 assn standard all material responses or astm a-331 assn standard all material responses |
| Surface Treatment: |
| Cadmium |
| Style Designator: |
| Threaded at small end |

NSN 5315-00-275-4990

Threaded Tapered Pin - Page 2 of 2



Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0