

View Online at <https://aerobasegroup.com/nsn/5315-00-276-9641>

First End Style:

Round

Second End Style:

Square

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.578 inches and 0.610 inches

Taper Length:

Between 1.234 inches and 1.266 inches

Taper Minor Diameter:

Between 0.603 inches and 0.607 inches

Taper Major Diameter:

0.660 inches

Hole Arrangement Style:

One end drilled

First Hole Diameter:

Between 0.106 inches and 0.116 inches

Distance From Centerline Of Hole To End Of Pin:

Between 0.391 inches and 0.422 inches

Grip Length:

Between 1.109 inches and 1.141 inches

Second End Relationship With First End:

Not identical

Thread Size:

0.500 inches

Taper:

0.500 per foot in inches

First End Location:

Round end

Material:

Steel comp 2330 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130

Material Specification:

Qq-s-689 federal specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6050 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6758 military specification 5th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification single treatment response

Style Designator:

Threaded at small end

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6049 spec.