## NSN 5315-00-282-1346

Headless Grooved Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-282-1346

view Online at https://aerobasegroup.com/nsn/5315-00-282-1346
First End Style:
Chamfered
Overall Length:
Between 1.140 inches and 1.160 inches
Diameter:
Between 0.310 inches and 0.311 inches
Effective Length:
Between 0.880 inches and 0.885 inches
Undercut Diameter:
Between 0.234 inches and 0.240 inches
Undercut Width:
Between 0.073 inches and 0.076 inches
Second Undercut Width:
Between 0.073 inches and 0.076 inches
Undercut Radius:
Between 0.026 inches and 0.046 inches
First End Taper Length:
Between 0.021 inches and 0.041 inches
Second End Relationship With First End:
Identical
Hardness Rating:
40.0 rockwell c and 45.0 rockwell c
First End Location:
Both ends
First End Taper Angle:
Between 40.0 degrees and 50.0 degrees
Surface Finish:
32.0 microinches shank end
Material:
Steel
Surface Treatment:
Phosphate
Surface Treatment Specification:
Mil-p-16232, type 1 military specification single treatment response
Style Designator:
Groove
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5315-00-282-1346

Headless Grooved Pin - Page 2 of 2



Fiig:

A212a0

Mil-std (military Standard):

Mil-p-16232 spec.