## NSN 5315-00-282-1347

Headless Grooved Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-282-1347

| First End Style:   |
|--|
| Chamfered  |
| Overall Length:  |
| Between 0.615 inches and 0.635 inches                                    |
| Diameter:  |
| Between 0.187 inches and 0.188 inches                                    |
| Effective Length:  |
| Between 0.500 inches and 0.510 inches                                    |
| Undercut Diameter:   |
| Between 0.1735 inches and 0.1765 inches                                  |
| Undercut Width:  |
| Between 0.017 inches and 0.019 inches                                    |
| First End Taper Length:  |
| 0.015 inches   |
| Second End Relationship With First End:                                  |
| Identical  |
| Hardness Rating:   |
| 45.0 rockwell c and 50.0 rockwell c                                      |
| First End Location:  |
| Both ends  |
| First End Taper Angle:   |
| 45.0 degrees   |
| Surface Finish:  |
| 32.0 microinches outside diameter  |
| Material:  |
| Steel  |
| Surface Treatment:   |
| Phosphate  |
| Surface Treatment Specification:   |
| Mil-p-16232, ty m, cl 1 military specification single treatment response |
| Style Designator:  |
| Groove   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A212a0   |
| Mil-std (military Standard):   |
| Mil-p-16232 spec.  |