

View Online at <https://aerobasegroup.com/nsn/5315-00-297-1157>

First End Style:

Chamfered

Head Style:

Flat

Diameter:

Between 0.435 inches and 0.436 inches

Effective Length:

0.197 inches

Undercut Diameter:

Between 0.417 inches and 0.427 inches

Under Head Length:

Between 3.302 inches and 3.322 inches

Undercut Width:

Between 0.046 inches and 0.056 inches

Hole Arrangement Style:

One end drilled

First Hole Diameter:

Between 0.1065 inches and 0.1115 inches

Distance From Centerline Of Hole To End Of Pin:

Between 3.052 inches and 3.057 inches

First End Taper Length:

Between 0.083 inches and 0.103 inches

Grip Length:

Between 0.250 inches and 0.255 inches

First End Taper Angle:

Between 43.0 degrees and 47.0 degrees

Pin Head Diameter:

Between 0.677 inches and 0.697 inches

Surface Finish:

63.0 microinches head outside diameter

Height:

Between 0.177 inches and 0.197 inches

Material:

Steel comp 1010 or steel comp 1015 or steel comp 1020 or steel comp 1030 or steel comp 1040 or steel

Material Specification:

Mil-s-16782 military specification 1st material response or mil-s-16782 military specification 2nd material response or mil-s-16788, cl c2 military specification 3rd material response or mil-s-16788, cl c3 military specification 4th material response or mil-s-16788, cl c4 military specification 5th material response or mil-s-890, cl 8 or cl bs military specification 6th material response

Style Designator:

Groove

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-s-16782 spec.