

View Online at <https://aerobasegroup.com/nsn/5315-00-297-1157>

**First End Style:**

Chamfered

**Head Style:**

Flat

**Diameter:**

Between 0.435 inches and 0.436 inches

**Effective Length:**

0.197 inches

**Undercut Diameter:**

Between 0.417 inches and 0.427 inches

**Under Head Length:**

Between 3.302 inches and 3.322 inches

**Undercut Width:**

Between 0.046 inches and 0.056 inches

**Hole Arrangement Style:**

One end drilled

**First Hole Diameter:**

Between 0.1065 inches and 0.1115 inches

**Distance From Centerline Of Hole To End Of Pin:**

Between 3.052 inches and 3.057 inches

**First End Taper Length:**

Between 0.083 inches and 0.103 inches

**Grip Length:**

Between 0.250 inches and 0.255 inches

**First End Taper Angle:**

Between 43.0 degrees and 47.0 degrees

**Pin Head Diameter:**

Between 0.677 inches and 0.697 inches

**Surface Finish:**

63.0 microinches head outside diameter

**Height:**

Between 0.177 inches and 0.197 inches

**Material:**

Steel comp 1010 or steel comp 1015 or steel comp 1020 or steel comp 1030 or steel comp 1040 or steel

**Material Specification:**

Mil-s-16782 military specification 1st material response or mil-s-16782 military specification 2nd material response or mil-s-16788, cl c2 military specification 3rd material response or mil-s-16788, cl c3 military specification 4th material response or mil-s-16788, cl c4 military specification 5th material response or mil-s-890, cl 8 or cl bs military specification 6th material response

**Style Designator:**

Groove

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-16782 spec.