

View Online at <https://aerobasegroup.com/nsn/5315-00-297-1441>

First End Style:

Radius

Head Style:

Bevel

Diameter:

Between 0.2485 inches and 0.2490 inches

Effective Length:

Between 0.464 inches and 0.474 inches

Undercut Diameter:

Between 0.213 inches and 0.223 inches

Under Head Length:

Between 0.578 inches and 0.609 inches

Undercut Width:

Between 0.031 inches and 0.062 inches

Hole Arrangement Style:

One end drilled

First Hole Diameter:

Between 0.062 inches and 0.066 inches

Distance From Centerline Of Hole To End Of Pin:

Between 0.078 inches and 0.109 inches

First End Corner Radius:

0.010 inches

Grip Length:

Between 0.495 inches and 0.505 inches

Pin Head Diameter:

Between 0.359 inches and 0.391 inches

Surface Finish:

32.0 microinches shank end

Height:

Between 0.047 inches and 0.078 inches

Material:

Steel comp 1020 or steel comp 1030

Material Specification:

Mil-s-16788, cl c2 military specification 1st material response or mil-s-16788, cl c3 military specification 2nd material response

Style Designator:

Groove

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-16788 spec.