## NSN 5315-00-298-1017



Threaded Tapered Pin - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5315-00-298-1017 First End Style: Oval **Second End Style:** Square **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.422 inches and 0.453 inches **Taper Length:** Between 1.734 inches and 1.766 inches **Taper Minor Diameter:** Between 0.203 inches and 0.207 inches **Taper Major Diameter:** 0.279 inches **Grip Length:** Between 1.609 inches and 1.641 inches Thready Qty Per Inch (tpi): 32 Second End Relationship With First End: Not identical **Thread Size:** 0.190 inches Taper: 0.500 per foot in inches First End Location: Oval end Material: Steel comp 2330 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 **Material Specification:** Qq-s-689 federal specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6050 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6758 military specification 5th material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** 

Qq-p-416, type 1, cl 3 federal specification single treatment response

**Style Designator:** 

Threaded at small end

**Thread Series Designator:** 

Unf

Shelf Life:

N/a

## NSN 5315-00-298-1017

Threaded Tapered Pin - Page 2 of 2



П	Init	7 1+	Measure:
u	,,,,,	v	wicasuic.

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6049 spec.