## NSN 5315-00-298-1030



Threaded Tapered Pin - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5315-00-298-1030 First End Style: Square **Second End Style:** Oval Thread Class: За **Thread Direction:** Right-hand Thread Length: Between 0.438 inches and 0.469 inches **Taper Length:** Between 1.609 inches and 1.641 inches **Taper Minor Diameter:** Between 0.315 inches and 0.319 inches **Taper Major Diameter:** 0.384 inches **Grip Length:** Between 1.484 inches and 1.516 inches Second End Relationship With First End: Not identical **Thread Size:** 0.250 inches Taper: 0.500 per foot in inches **First End Location:** Threaded end Material: Steel or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 **Material Specification:** Qq-s-681 federal specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6050 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6758 military specification 5th material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification single treatment response **Style Designator:** Threaded at small end **Thread Series Designator:** 

--

Unf

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5315-00-298-1030

Threaded Tapered Pin - Page 2 of 2



Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6049 spec.