

View Online at <https://aerobasegroup.com/nsn/5315-00-298-9902>

First End Style:

Chamfered

Shank Length:

Between 1.672 inches and 1.703 inches

Shoulder Diameter:

Between 0.465 inches and 0.467 inches

Shank Diameter:

Between 0.465 inches and 0.467 inches

Overall Length:

Between 6.734 inches and 6.766 inches

Undercut Diameter:

Between 0.360 inches and 0.365 inches

Undercut Width:

Between 0.375 inches and 0.391 inches

Second Undercut Width:

Between 0.375 inches and 0.391 inches

Second Undercut Diameter:

Between 0.360 inches and 0.365 inches

Hole Arrangement Style:

Both end drilled

First Hole Diameter:

0.110 inches

Second Hole Diameter:

0.110 inches

Distance From Centerline Of Hole To End Of Pin:

Between 0.266 inches and 0.297 inches

Center To Center Distance Between Holes:

Between 6.172 inches and 6.203 inches

First End Taper Length:

Between 0.016 inches and 0.047 inches

Second End Relationship With First End:

Identical

Second Shank Diameter:

Between 0.465 inches and 0.467 inches

First End Location:

Both ends

First End Taper Angle:

45.0 degrees

Second Shank Length:

Between 1.672 inches and 1.703 inches

Material:

Copper alloy 360

Material Specification:

Aa-b-626 comp 22 federal specification single material response

Style Designator:

Undercut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0