## NSN 5315-00-298-9902

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-298-9902

First End Style:

Chamfered

**Shank Length:** 

Between 1.672 inches and 1.703 inches

Shoulder Diameter:

Between 0.465 inches and 0.467 inches

**Shank Diameter:** 

Between 0.465 inches and 0.467 inches

**Overall Length:** 

Between 6.734 inches and 6.766 inches

**Undercut Diameter:** 

Between 0.360 inches and 0.365 inches

**Undercut Width:** 

Between 0.375 inches and 0.391 inches

**Second Undercut Width:** 

Between 0.375 inches and 0.391 inches

**Second Undercut Diameter:** 

Between 0.360 inches and 0.365 inches

**Hole Arrangement Style:** 

Both end drilled

First Hole Diameter:

0.110 inches

**Second Hole Diameter:** 

0.110 inches

**Distance From Centerline Of Hole To End Of Pin:** 

Between 0.266 inches and 0.297 inches

**Center To Center Distance Between Holes:** 

Between 6.172 inches and 6.203 inches

First End Taper Length:

Between 0.016 inches and 0.047 inches

Second End Relationship With First End:

Identical

Second Shank Diameter:

Between 0.465 inches and 0.467 inches

**First End Location:** 

Both ends

First End Taper Angle:

45.0 degrees

Second Shank Length:

Between 1.672 inches and 1.703 inches

Material:

Copper alloy 360

## NSN 5315-00-298-9902

Headless Shoulder Pin - Page 2 of 2



М	ater	ial	Sp	ecifi	icati	on:

Aa-b-626 comp 22 federal specification single material response

**Style Designator:** 

Undercut

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A212a0