NSN 5315-00-301-3685

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-301-3685

First End Style:
Chamfered
Second End Style:
Slotted
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.990 inches and 1.010 inches
Shank Length:
Between 0.490 inches and 0.510 inches
Shoulder Diameter:
Between 0.240 inches and 0.260 inches
Shank Diameter:
Between 0.117 inches and 0.122 inches
Overall Length:
Between 4.927 inches and 4.947 inches
Second End Slot Width:
Between 0.052 inches and 0.072 inches
First End Taper Length:
Between 0.052 inches and 0.072 inches
Second End Slot Depth:
Between 0.068 inches and 0.088 inches
Second End Relationship With First End:
Not identical
Thread Size:
0.250 inches
Second Shank Diameter:
Between 0.177 inches and 0.197 inches
First End Location:
Slot end
First End Taper Angle:
30.0 degrees
Second Shank Length:
Between 3.427 inches and 3.447 inches
Special Features:
Round slotted end
Material:
Steel comp 1112
Material Specification:
Sae assn standard single material response

NSN 5315-00-301-3685

Headless Shoulder Pin - Page 2 of 2



Style Designator:
Shoulder
Thread Series Designator:
Unf
Shelf Life:
N/a

Demilitarization:

Unit Of Measure:

No

Fiig:

A212a0