

View Online at <https://aerobasegroup.com/nsn/5315-00-301-3685>

**First End Style:**

Chamfered

**Second End Style:**

Slotted

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.990 inches and 1.010 inches

**Shank Length:**

Between 0.490 inches and 0.510 inches

**Shoulder Diameter:**

Between 0.240 inches and 0.260 inches

**Shank Diameter:**

Between 0.117 inches and 0.122 inches

**Overall Length:**

Between 4.927 inches and 4.947 inches

**Second End Slot Width:**

Between 0.052 inches and 0.072 inches

**First End Taper Length:**

Between 0.052 inches and 0.072 inches

**Second End Slot Depth:**

Between 0.068 inches and 0.088 inches

**Second End Relationship With First End:**

Not identical

**Thread Size:**

0.250 inches

**Second Shank Diameter:**

Between 0.177 inches and 0.197 inches

**First End Location:**

Slot end

**First End Taper Angle:**

30.0 degrees

**Second Shank Length:**

Between 3.427 inches and 3.447 inches

**Special Features:**

Round slotted end

**Material:**

Steel comp 1112

**Material Specification:**

Sae assn standard single material response

**Style Designator:**

Shoulder

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0