NSN 5315-00-303-2936

Headless Shoulder Pin - Page 1 of 2

First End Style: Chamfered

Passivate



View Online at https://aerobasegroup.com/nsn/5315-00-303-2936

Second End Style:
Pointed
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.351 inches
Shank Length:
0.531 inches
Shoulder Width Across Flats:
0.750 inches
Shank Diameter:
Between 0.255 inches and 0.256 inches
Overall Length:
1.450 inches
First End Taper Length:
Between 0.040 inches and 0.070 inches
Second End Relationship With First End:
Not identical
Thread Size:
0.250 inches
First End Location:
Threaded end
First End Taper Angle:
45.0 degrees
Surface Finish:
125.000 microinches
Second End Taper Angle:
40.0 degrees
Second Shank Length:
0.789 inches
Special Features:
0.060 in. Radius on pointed shank
Material:
Iron alloy 660
Material Specification:
Ams 5735 assn standard single material response
Surface Treatment:

NSN 5315-00-303-2936

Headless Shoulder Pin - Page 2 of 2



Surface Treatment Specification:
${\sf Ps13001, fscm\ 76301\ mfr\ ref\ single\ treatment\ response}$
Style Designator:
Shoulder
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A212a0