

View Online at <https://aerobasegroup.com/nsn/5315-00-304-2995>

**First End Style:**

Square

**Shank Length:**

0.610 inches

**Shoulder Diameter:**

Between 0.434 inches and 0.435 inches

**Shank Diameter:**

Between 0.868 inches and 0.869 inches

**Overall Length:**

4.000 inches

**Undercut Diameter:**

0.688 inches

**Undercut Width:**

Between 0.120 inches and 0.130 inches

**Second Undercut Width:**

Between 0.120 inches and 0.130 inches

**Second Undercut Diameter:**

0.688 inches

**Second End Relationship With First End:**

Identical

**Shear Strength:**

180000 single pounds per square inch

**Second Shank Diameter:**

Between 0.868 inches and 0.869 inches

**First End Location:**

Both ends

**Second Shank Length:**

1.075 inches

**Product Name:**

Pin, crew door hinge

**Special Features:**

Dimensions apply after solid film lub plating; pin has two shoulders, one on each end and a third should that is undercut in the center

**Material:**

Steel comp 8740

**Material Specification:**

Mil-s-6049, condc-4 military specification single material response

**Style Designator:**

Undercut

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6049 spec.