

View Online at <https://aerobasegroup.com/nsn/5315-00-310-1248>

**First End Style:**

Chamfered

**Second End Style:**

Chamfered

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.840 inches

**Shank Length:**

Between 0.985 inches and 1.015 inches

**Shoulder Diameter:**

Between 0.6226 inches and 0.6239 inches

**Shank Diameter:**

Between 0.368 inches and 0.375 inches

**Overall Length:**

5.675 inches

**First End Taper Length:**

Between 0.050 inches and 0.080 inches

**Second End Taper Length:**

0.740 inches

**Second End Relationship With First End:**

Not identical

**Thread Size:**

0.375 inches

**First End Location:**

Threaded end

**First End Taper Angle:**

45.0 degrees

**Surface Finish:**

40.0 microinches shoulder bearing surface

**Special Features:**

Flat surface on shank 0.500 in. Across flats; 0.380 in. W

**Material:**

Steel comp 8630

**Material Specification:**

Mil-s-6050, cond c-1 military specification single material response

**Surface Treatment:**

Chromium shank

**Style Designator:**

Shoulder

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6050 spec.