

View Online at <https://aerobasegroup.com/nsn/5315-00-316-0818>

**First End Style:**

Chamfered

**Overall Length:**

7.250 inches

**Diameter:**

Between 0.497 inches and 0.499 inches

**Effective Length:**

Between 6.682 inches and 6.692 inches

**Undercut Diameter:**

Between 0.421 inches and 0.426 inches

**Undercut Width:**

0.250 inches

**Undercut Radius:**

Between 0.125 inches and 0.141 inches

**Hole Arrangement Style:**

Both end drilled

**First Hole Diameter:**

Between 0.186 inches and 0.187 inches

**Second Hole Diameter:**

Between 0.129 inches and 0.131 inches

**Distance From Centerline Of Hole To End Of Pin:**

0.609 inches

**Center To Center Distance Between Holes:**

0.610 inches

**First End Taper Length:**

0.031 inches

**Features Provided:**

Casehardened

**Second End Relationship With First End:**

Identical

**Hardness Rating:**

40.0 rockwell c and 50.0 rockwell c

**First End Location:**

Both ends

**First End Taper Angle:**

45.0 degrees

**Material:**

Steel comp 1040 or steel comp 1045

**Material Specification:**

Qq-s-633 federal specification all material responses

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0