

View Online at <https://aerobasegroup.com/nsn/5315-00-316-0818>

First End Style:

Chamfered

Overall Length:

7.250 inches

Diameter:

Between 0.497 inches and 0.499 inches

Effective Length:

Between 6.682 inches and 6.692 inches

Undercut Diameter:

Between 0.421 inches and 0.426 inches

Undercut Width:

0.250 inches

Undercut Radius:

Between 0.125 inches and 0.141 inches

Hole Arrangement Style:

Both end drilled

First Hole Diameter:

Between 0.186 inches and 0.187 inches

Second Hole Diameter:

Between 0.129 inches and 0.131 inches

Distance From Centerline Of Hole To End Of Pin:

0.609 inches

Center To Center Distance Between Holes:

0.610 inches

First End Taper Length:

0.031 inches

Features Provided:

Casehardened

Second End Relationship With First End:

Identical

Hardness Rating:

40.0 rockwell c and 50.0 rockwell c

First End Location:

Both ends

First End Taper Angle:

45.0 degrees

Material:

Steel comp 1040 or steel comp 1045

Material Specification:

Qq-s-633 federal specification all material responses

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0