NSN 5315-00-316-5565

Headless Straight Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-316-5565

First End Style:ChamferedHole Arrangement Style:One end drilledFirst Hole Diameter:Between 0.190 inches and 0.196 inchesDistance From Centerline Of Hole To End Of Pin:1.795 inchesPinlength:3.200 inchesPindiameter:Between 0.7485 inches and 0.7494 inchesFirst End Taper Length:0.030 inchesSecond End Relationship With First End:IdenticalFirst End Taper Angle:45.0 degreesMaterial:SteelSurface Treatment:ChromiumShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:A212a0	
Hole Arrangement Style: One end drilled First Hole Diameter: Between 0.190 inches and 0.196 inches Distance From Centerline Of Hole To End Of Pin: 1.795 inches Pinlength: 3.200 inches Pindiameter: Between 0.7485 inches and 0.7494 inches First End Taper Length: 0.030 inches Second End Relationship With First End: Identical First End Taper Angle: 45.0 degrees Material: Steel Surface Treatment: Chromium Shelf Life: N/a Unit Of Measure: Penilitarization: No Fiig:	First End Style:
One end drilled First Hole Diameter: Between 0.190 inches and 0.196 inches Distance From Centerline Of Hole To End Of Pin: 1.795 inches Pinlength: 3.200 inches Pindiameter: Between 0.7485 inches and 0.7494 inches First End Taper Length: 0.030 inches Second End Relationship With First End: Identical First End Taper Angle: 45.0 degrees Material: Steel Surface Treatment: Chromium Shelf Life: N/a Unit Of Measure: Demilitarization: No	Chamfered
First Hole Diameter: Between 0.190 inches and 0.196 inches Distance From Centerline Of Hole To End Of Pin: 1.795 inches Pinlength: 3.200 inches Pindiameter: Between 0.7485 inches and 0.7494 inches First End Taper Length: 0.030 inches Second End Relationship With First End: Identical First End Taper Angle: 45.0 degrees Material: Steel Surface Treatment: Chromium Shelf Life: N/a Unit Of Measure: Demilitarization: No	Hole Arrangement Style:
Between 0.190 inches and 0.196 inches Distance From Centerline Of Hole To End Of Pin: 1.795 inches Pinlength: 3.200 inches Pindiameter: Between 0.7485 inches and 0.7494 inches First End Taper Length: 0.030 inches Second End Relationship With First End: Identical First End Taper Angle: 45.0 degrees Material: Steel Surface Treatment: Chromium Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	One end drilled
Distance From Centerline Of Hole To End Of Pin:1.795 inchesPinlength:3.200 inchesPindiameter:Between 0.7485 inches and 0.7494 inchesFirst End Taper Length:0.030 inchesSecond End Relationship With First End:IdenticalFirst End Taper Angle:45.0 degreesMaterial:SteelSurface Treatment:ChromiumShelf Life:N/aTot Of Measure:Demilitarization:NoFiig:	First Hole Diameter:
1.795 inches Pinlength: 3.200 inches Pindiameter: Between 0.7485 inches and 0.7494 inches First End Taper Length: 0.030 inches Second End Relationship With First End: Identical First End Taper Angle: 45.0 degrees Material: Steel Surface Treatment: Chromium Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 0.190 inches and 0.196 inches
Pinlength: 3.200 inches Pindiameter: Between 0.7485 inches and 0.7494 inches First End Taper Length: 0.030 inches Second End Relationship With First End: Identical First End Taper Angle: 45.0 degrees Material: Steel Surface Treatment: Chromium Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Distance From Centerline Of Hole To End Of Pin:
3.200 inches Pindiameter: Between 0.7485 inches and 0.7494 inches First End Taper Length: 0.030 inches Second End Relationship With First End: Identical First End Taper Angle: 45.0 degrees Material: Steel Surface Treatment: Chromium Shelf Life: N/a Unit Of Measure: Demilitarization: No	1.795 inches
Pindiameter:Between 0.7485 inches and 0.7494 inchesFirst End Taper Length:0.030 inchesSecond End Relationship With First End:IdenticalFirst End Taper Angle:45.0 degreesMaterial:SteelSurface Treatment:ChromiumShelf Life:N/aDemilitarization:NoFig:	Pinlength:
Between 0.7485 inches and 0.7494 inches First End Taper Length: 0.030 inches Second End Relationship With First End: Identical First End Taper Angle: 45.0 degrees Material: Steel Surface Treatment: Chromium Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	3.200 inches
First End Taper Length: 0.030 inches Second End Relationship With First End: Identical First End Taper Angle: 45.0 degrees Material: 45.0 degrees Material: Steel Surface Treatment: Chromium Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Pindiameter:
0.030 inches Second End Relationship With First End: Identical First End Taper Angle: 45.0 degrees Material: Steel Surface Treatment: Chromium Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 0.7485 inches and 0.7494 inches
Second End Relationship With First End: Identical First End Taper Angle: 45.0 degrees Material: Steel Surface Treatment: Chromium Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	First End Taper Length:
Identical First End Taper Angle: 45.0 degrees Material: Steel Surface Treatment: Chromium Shelf Life: N/a Unit Of Measure: Fig:	0.030 inches
First End Taper Angle: 45.0 degrees Material: Steel Surface Treatment: Chromium Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Second End Relationship With First End:
45.0 degrees Material: Steel Surface Treatment: Chromium Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Identical
Material:SteelSurface Treatment:ChromiumShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	First End Taper Angle:
Steel Surface Treatment: Chromium Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	45.0 degrees
Surface Treatment: Chromium Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material:
Chromium Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Steel
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Surface Treatment:
N/a Unit Of Measure: Demilitarization: No Fiig:	Chromium
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
Demilitarization: No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
A212a0	Fiig:
	A212a0