## NSN 5315-00-316-5579

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-316-5579 First End Style: Chamfered Second End Style: Chamfered **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.458 inches and 0.468 inches **Shank Length:** 0.600 inches **Shoulder Diameter:** Between 0.496 inches and 0.498 inches **Shank Diameter:** 0.410 inches **Overall Length:** 2.095 inches First End Taper Length: 0.030 inches **Second End Taper Length:** 0.060 inches Second End Relationship With First End: Not identical **Thread Size:** 0.250 inches **First End Location:** Shoulder end First End Taper Angle: 30.0 degrees **Second End Taper Angle:** 45.0 degrees Material: Steel comp 4340 **Material Specification:** Mil-s-5000 comp 4340 cond e4 military specification single material response **Surface Treatment:** Cadmium

**Surface Treatment Specification:** 

Lc+77-2035 mfr ref single treatment response

**Style Designator:** 

Shoulder

## NSN 5315-00-316-5579

Headless Shoulder Pin - Page 2 of 2



| Thread Series Designator: |
|---------------------------|
| Unjf                      |
| Shelf Life:               |
| N/a                       |
| Unit Of Measure:          |
|                           |
| Demilitarization:         |
| No                        |
| Fiig:                     |
| A212a0                    |

Mil-std (military Standard):

Mil-s-5000 spec.