NSN 5315-00-316-6059

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-316-6059

First End Style:
Chamfered
Second End Style:
Pointed
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.500 inches
Shank Length:
0.500 inches
Shoulder Diameter:
0.625 inches
Shank Diameter:
0.312 inches
Overall Length:
Between 1.960 inches and 1.990 inches
First End Taper Length:
0.047 inches
Second End Taper Length:
0.500: 1
0.500 inches
Second End Relationship With First End:
Second End Relationship With First End:
Second End Relationship With First End: Not identical
Second End Relationship With First End: Not identical Thread Size:
Second End Relationship With First End: Not identical Thread Size: 0.312 inches
Second End Relationship With First End: Not identical Thread Size: 0.312 inches Second Shank Diameter:
Second End Relationship With First End: Not identical Thread Size: 0.312 inches Second Shank Diameter: Between 0.436 inches and 0.438 inches
Second End Relationship With First End: Not identical Thread Size: 0.312 inches Second Shank Diameter: Between 0.436 inches and 0.438 inches First End Location:
Second End Relationship With First End: Not identical Thread Size: 0.312 inches Second Shank Diameter: Between 0.436 inches and 0.438 inches First End Location: Threaded end
Second End Relationship With First End: Not identical Thread Size: 0.312 inches Second Shank Diameter: Between 0.436 inches and 0.438 inches First End Location: Threaded end First End Taper Angle:
Second End Relationship With First End: Not identical Thread Size: 0.312 inches Second Shank Diameter: Between 0.436 inches and 0.438 inches First End Location: Threaded end First End Taper Angle: 45.0 degrees
Second End Relationship With First End: Not identical Thread Size: 0.312 inches Second Shank Diameter: Between 0.436 inches and 0.438 inches First End Location: Threaded end First End Taper Angle: 45.0 degrees Surface Finish:
Second End Relationship With First End: Not identical Thread Size: 0.312 inches Second Shank Diameter: Between 0.436 inches and 0.438 inches First End Location: Threaded end First End Taper Angle: 45.0 degrees Surface Finish: 8.0 microinches shank end
Second End Relationship With First End: Not identical Thread Size: 0.312 inches Second Shank Diameter: Between 0.436 inches and 0.438 inches First End Location: Threaded end First End Taper Angle: 45.0 degrees Surface Finish: 8.0 microinches shank end Second End Taper Angle:
Second End Relationship With First End: Not identical Thread Size: 0.312 inches Second Shank Diameter: Between 0.436 inches and 0.438 inches First End Location: Threaded end First End Taper Angle: 45.0 degrees Surface Finish: 8.0 microinches shank end Second End Taper Angle: 40.0 degrees
Second End Relationship With First End: Not identical Thread Size: 0.312 inches Second Shank Diameter: Between 0.436 inches and 0.438 inches First End Location: Threaded end First End Taper Angle: 45.0 degrees Surface Finish: 8.0 microinches shank end Second End Taper Angle: 40.0 degrees Second Shank Length:
Second End Relationship With First End: Not identical Thread Size: 0.312 inches Second Shank Diameter: Between 0.436 inches and 0.438 inches First End Location: Threaded end First End Taper Angle: 45.0 degrees Surface Finish: 8.0 microinches shank end Second End Taper Angle: 40.0 degrees Second Shank Length: 1.375 inches
Second End Relationship With First End: Not identical Thread Size: 0.312 inches Second Shank Diameter: Between 0.436 inches and 0.438 inches First End Location: Threaded end First End Taper Angle: 45.0 degrees Surface Finish: 8.0 microinches shank end Second End Taper Angle: 40.0 degrees Second Shank Length: 1.375 inches Special Features:

NSN 5315-00-316-6059

Headless Shoulder Pin - Page 2 of 2



Material Specification:
Ams 5643 assn standard single material response
Surface Treatment:
Passivate
Style Designator:
Shoulder
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A212a0