NSN 5315-00-320-0368

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-320-0368

First End Style:
Chamfered
Second End Style:
Round
Shank Length:
Between 0.240 inches and 0.260 inches
Shoulder Diameter:
Between 0.140 inches and 0.160 inches
Shank Diameter:
Between 0.1232 inches and 0.1234 inches
Overall Length:
Between 2.490 inches and 2.510 inches
Undercut Diameter:
Between 0.010 inches and 0.030 inches
Undercut Width:
Between 0.020 inches and 0.040 inches
Second Undercut Width:
Between 0.020 inches and 0.040 inches
Second Undercut Diameter:
Between 0.010 inches and 0.030 inches
First End Taper Length:
Between 0.021 inches and 0.041 inches
Second End Relationship With First End:
Not identical
Second Shank Diameter:
Between 0.1232 inches and 0.1234 inches
First End Location:
Shank end
First End Taper Angle:
Between 44.0 degrees and 46.0 degrees
First End Outer Radius:
Between 0.010 inches and 0.030 inches
Second Shank Length:
Between 0.240 inches and 0.260 inches
Special Features:
Shoulder 20 pitch diamond knurled and undercut between shoulder and shank 0.03 in. W by 0.02 in. Deep
Material:
Steel comp 416
Material Specification:
Qq-s-763, cond a federal specification single material response
Style Designator:
Undercut

NSN 5315-00-320-0368

Headless Shoulder Pin - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

