NSN 5315-00-328-5885

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-328-5885

First End Style:
Chamfered
Second End Style:
Chamfered
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.302 inches and 0.322 inches
Shank Length:
Between 0.302 inches and 0.322 inches
Shoulder Diameter:
Between 0.410 inches and 0.470 inches
Shank Diameter:
0.190 inches
Overall Length:
Between 0.771 inches and 0.791 inches
First End Taper Length:
Between 0.020 inches and 0.080 inches
Second End Taper Length:
Between 0.030 inches and 0.090 inches
Thready Qty Per Inch (tpi):
24
Second End Relationship With First End:
Not identical
Thread Size:
0.190 inches
Second Shank Diameter:
Between 0.301 inches and 0.306 inches
First End Location:
Both ends
First End Taper Angle:
Between 44.5 degrees and 45.5 degrees
Second End Taper Angle:
Between 44.5 degrees and 45.5 degrees
Second Shank Length:
Between 0.288 inches and 0.308 inches
Special Features:
Large diameter end slotted 0.03 to 0.09 in. W by 0.115 to 0.135 in. Deep
Material:
Steel comp 303se

NSN 5315-00-328-5885

Headless Shoulder Pin - Page 2 of 2

Fiig: A212a0



Material Specification:
Qq-s-764, type 303se, cond b federal specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Style Designator:
Shoulder
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No