## NSN 5315-00-328-8214

Headless Straight Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-328-8214

First End Style:         Square         Hole Arrangement Style:         Both end drilled         First Hole Diameter:         0.078 inches         Second Hole Diameter:         0.078 inches         Distance From Centerline Of Hole To End Of Pin:         0.114 inches         Center To Center Distance Between Holes:         0.834 inches         Pinlength:         1.062 inches         Pindiameter:         0.3110 inches         Second End Relationship With First End:         Identical         Hardness Rating:         35.0 rockwell c         Material:         Steel         Material Specification:         Ams 5758 assn standard single material response         Surface Treatment:         Passivate         Surface Treatment Specification:         Qu-p-35 federal specification single treatment response
Hole Arrangement Style:Both end drilledFirst Hole Diameter:0.078 inchesSecond Hole Diameter:0.078 inchesDistance From Centerline Of Hole To End Of Pin:0.114 inchesCenter To Center Distance Between Holes:0.834 inchesPinlength:1.062 inchesPindiameter:0.3110 inchesSecond End Relationship With First End:IdenticalHardness Rating:35.0 rockwell cMaterial:SteelMaterial Specification:Ams 5758 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:
Both end drilledFirst Hole Diameter:0.078 inchesSecond Hole Diameter:0.078 inchesDistance From Centerline Of Hole To End Of Pin:0.114 inchesCenter To Center Distance Between Holes:0.834 inchesPinlength:1.062 inchesPindiameter:0.3110 inchesSecond End Relationship With First End:IdenticalHardness Rating:35.0 rockwell cMaterial:SteelMaterial Specification:Ams 5758 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:
0.078 inchesSecond Hole Diameter:0.078 inchesDistance From Centerline Of Hole To End Of Pin:0.114 inchesCenter To Center Distance Between Holes:0.834 inchesPinlength:1.062 inchesPindiameter:0.3110 inchesSecond End Relationship With First End:IdenticalHardness Rating:35.0 rockwell cMaterial:SteelMaterial Specification:Arns 5758 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:
Second Hole Diameter: 0.078 inches Distance From Centerline Of Hole To End Of Pin: 0.114 inches Center To Center Distance Between Holes: 0.834 inches Pinlength: 1.062 inches Pindiameter: 0.3110 inches Second End Relationship With First End: Identical Hardness Rating: 35.0 rockwell c Material: Steel Material Specification: Ams 5758 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
0.078 inches Distance From Centerline Of Hole To End Of Pin: 0.114 inches Center To Center Distance Between Holes: 0.834 inches Distance Between Holes: 0.834 inches Pinlength: 1.062 inches Pinlength: 1.062 inches Pindiameter: 0.3110 inches Second End Relationship With First End: 0.3110 inches Second End Relationship With First End: Identical Hardness Rating: 35.0 rockwell c Haterial Steel Material Steel Material Specification: Ams 5758 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
Distance From Centerline Of Hole To End Of Pin:0.114 inchesCenter To Center Distance Between Holes:0.834 inchesPinlength:1.062 inchesPindiameter:0.3110 inchesSecond End Relationship With First End:IdenticalHardness Rating:35.0 rockwell cMaterial:SteelMaterial Specification:Ams 5758 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:
0.114 inches Center To Center Distance Between Holes: 0.834 inches Pinlength: 1.062 inches Pindiameter: 0.3110 inches Second End Relationship With First End: 0.3110 inches Second End Relationship With First End: Identical Hardness Rating: 35.0 rockwell c Hardness Rating: 35.0 rockwell c Material: Steel Material Specification: Ams 5758 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
Center To Center Distance Between Holes:0.834 inchesPinlength:1.062 inchesPindiameter:0.3110 inchesSecond End Relationship With First End:IdenticalHardness Rating:35.0 rockwell cMaterial:SteelMaterial Specification:Ams 5758 assn standard single material responseSurface Treatment:PassivateSurface Treatment:PassivateSurface Treatment Specification:
0.834 inches Pinlength: 1.062 inches Pindiameter: 0.3110 inches Second End Relationship With First End: 1dentical Hardness Rating: 35.0 rockwell c Material: Steel Material Specification: Ams 5758 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
Pinlength:1.062 inchesPindiameter:0.3110 inchesSecond End Relationship With First End:IdenticalHardness Rating:35.0 rockwell cMaterial:SteelMaterial Specification:Ams 5758 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:
1.062 inches Pindiameter: 0.3110 inches Second End Relationship With First End: Identical Hardness Rating: 35.0 rockwell c Material: Steel Material Specification: Ams 5758 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
Pindiameter:0.3110 inchesSecond End Relationship With First End:IdenticalHardness Rating:35.0 rockwell cMaterial:SteelMaterial Specification:Ams 5758 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:
0.3110 inches Second End Relationship With First End: Identical Hardness Rating: 35.0 rockwell c Material: Steel Material Specification: Ams 5758 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
Second End Relationship With First End: Identical Hardness Rating: 35.0 rockwell c Material: Steel Material Specification: Ams 5758 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
Identical Hardness Rating: 35.0 rockwell c Material: Steel Material Specification: Ams 5758 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
Hardness Rating: 35.0 rockwell c Material: Steel Material Specification: Ams 5758 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
35.0 rockwell c Material: Steel Material Specification: Ams 5758 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
Material:         Steel         Material Specification:         Ams 5758 assn standard single material response         Surface Treatment:         Passivate         Surface Treatment Specification:
Steel Material Specification: Ams 5758 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
Material Specification:Ams 5758 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:
Ams 5758 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
Surface Treatment: Passivate Surface Treatment Specification:
Passivate Surface Treatment Specification:
Surface Treatment Specification:
-
Qq-p-35 federal specification single treatment response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A212a0