

View Online at <https://aerobasegroup.com/nsn/5315-00-331-9429>

**First End Style:**

Chamfered

**Second End Style:**

Pointed

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.438 inches

**Shank Length:**

0.438 inches

**Shoulder Diameter:**

0.438 inches

**Shank Diameter:**

0.190 inches

**Overall Length:**

1.000 inches

**First End Taper Length:**

0.031 inches

**Second End Taper Length:**

0.188 inches

**Second End Relationship With First End:**

Not identical

**Thread Size:**

0.190 inches

**Second Shank Diameter:**

Between 0.246 inches and 0.252 inches

**First End Location:**

Threaded end

**First End Taper Angle:**

45.0 degrees

**Second End Taper Angle:**

60.0 degrees

**Second Shank Length:**

0.500 inches

**Special Features:**

Pointed end has 0.031 in. Spherical radius, and flat on one side 0.188 in. Across 0.312 in. Lg

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758 cond f military specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541 military specification single treatment response

**Style Designator:**

Shoulder

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.