

View Online at <https://aerobasegroup.com/nsn/5315-00-332-3885>

**First End Style:**

Chamfered

**Second End Style:**

Pointed

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.420 inches

**Shank Length:**

0.375 inches

**Shoulder Width Across Flats:**

0.375 inches

**Shank Diameter:**

Between 0.239 inches and 0.240 inches

**Overall Length:**

1.125 inches

**First End Taper Length:**

0.050 inches

**Second End Taper Length:**

0.120 inches

**Thready Qty Per Inch (tpi):**

28

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

35.0 rockwell c and 43.0 rockwell c

**Thread Size:**

0.250 inches

**Second Shank Diameter:**

Between 0.243 inches and 0.250 inches

**First End Location:**

Threaded end

**First End Taper Angle:**

45.0 degrees

**Surface Finish:**

125.000 microinches

**Second End Taper Angle:**

90.0 degrees

**Second Shank Length:**

0.500 inches

**Material:**

Steel comp 630

**Material Specification:**

Ams 5643 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Style Designator:**

Shoulder

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0