NSN 5315-00-332-4933

Headed Shoulder Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-332-4933

First End Style: Charlered Head Style: Flat Under Head Length: 1.687 inches First Step Diameter: Between 0.370 inches and 0.375 inches First Step Langth: Between 0.130 inches and 0.135 inches Second Step Length: Between 0.244 inches and 0.249 inches Second Step Length: 1.554 inches First End Taper Length: 0.063 inches First End Taper Length: 0.063 inches Pint Head Diameter: 1.000 inches Height: 0.063 inches Material: Steel comp 4130 Material Specification: Mil-s-6758, cond d military specification single material response Surface Treatment: Chailum Style Designator: Shoulder Sheif Life: Na Tif Pint Interization: Na Stel Comp 4130 Mil-s-6758, cond d military specification single material response Surface Treatment: <td< th=""><th>First Find Otales</th></td<>	First Find Otales
Head Style:FlatUnder Head Length:1.687 inchesFirst Step Diameter:Between 0.370 inches and 0.375 inchesFirst Step Length:Between 0.130 inches and 0.135 inchesSecond Step Diameter:Between 0.244 inches and 0.249 inchesSecond Step Length:1.554 inchesFirst End Taper Length:0.063 inchesFirst End Taper Length:0.063 inchesPin Head Diameter:1.000 inchesHeight:0.003 inchesBetareit:2.000 inchesHeight:0.003 inchesHeight:0.003 inchesHeight:0.004 inchesHold Diameter:1.000 inchesHeight:0.011 inchesHeight:0.021 inchesHeight:0.031 inchesHeight:0.041 inchesHeight:0.052 inchesStel comp 4130Material:StolderStolderStolderStolderShoulderShoulderNaHiller:NaDiameter:NaStolder:NaShoulder:NaShoulder:Stolder:Shoulder:Shoulder:Shoulder:Shoulder:Shoulder:Shoulder:Shoulder:Shoulder:Shoulder:Shoulder:Shoulde	-
Flat Under Head Length: 1.687 inches First Step Diameter: Between 0.370 inches and 0.375 inches First Step Length: Between 0.130 inches and 0.135 inches Second Step Diameter: Between 0.244 inches and 0.249 inches Between 0.244 inches and 0.249 inches Second Step Length: 1.554 inches First End Taper Length: 0.063 inches First End Taper Angle: 45.0 degrees Pin Head Diameter: 1.000 inches Height: 0.063 inches Material: Steel comp 4130 Material Specification: Miles-6758, cond d military specification single material response Strif Common Shoulder Shoulder Shoulder Na Miles Argen: Na Stel Comp 4130 Material Specification: Single Scond d military specification single material response Strif Common Shoulder	
Under Head Length: 1.687 inches First Step Diameter: Between 0.370 inches and 0.375 inches First Step Length: Between 0.130 inches and 0.135 inches Second Step Diameter: Between 0.244 inches and 0.249 inches Second Step Length: 1.554 inches First End Taper Length: 0.063 inches First End Taper Angle: 45.0 degrees Pin Head Diameter: 1.000 inches Height: 0.063 inches Material Specification: Miles-6758, cond d military specification single material response Surface Treatment: Cadmium Shouldar Shouldar Shouldar Shouldar Na Unt Of Measure: Na Fing: Autacial Surface Treatment: Na Shouldar Shouldar Shouldar Shouldar Shouldar Shouldar Shouldar Shouldar <td></td>	
1.687 inches First Step Diameter: Between 0.370 inches and 0.375 inches First Step Length: Between 0.130 inches and 0.135 inches Second Step Diameter: Between 0.244 inches and 0.249 inches Second Step Length: 1.554 inches First End Taper Length: 0.063 inches First End Taper Angle: 45.0 degrees Pin Head Diameter: 1.000 inches Height: 0.063 inches Material: Steel comp 4130 Material Specification: Mil-s-6758, cond d military specification single material response Surface Treatment: Scholder Shoulder Shoulder<	
First Step Diameter: Between 0.370 inches and 0.375 inches First Step Length: Between 0.130 inches and 0.135 inches Second Step Diameter: Between 0.244 inches and 0.249 inches Second Step Length: 1.554 inches First End Taper Length: 0.063 inches First End Taper Angle: 45.0 degrees Pin Head Diameter: 1.000 inches Height: 0.063 inches Material: Steel comp 4130 Material Steel comp 4130 Mil-s-6758, cond d military specification single material response Style Designator: Shoulder Style Colognator: Natorial Didf Measure: - Pinellitarization: Na Stel Colognator: Shoulder Shoulder Stel Stel Stel Stel Stel Stel Stel Stel	
Between 0.370 inches and 0.375 inches First Step Length: Between 0.130 inches and 0.135 inches Second Step Diameter: Between 0.244 inches and 0.249 inches Second Step Length: 1.554 inches First End Taper Length: 0.063 inches First End Taper Angle: 45.0 degrees Pin Head Diameter: 1.000 inches Height: 0.063 inches Material: Steel comp 4130 Material: Steel comp 4130 Material: Cadmium Strike Treatment: Cadmium Steel fice: Na Steel Iffe: Na Stold meiltary specification single material response Strike Treatment: Cadmium Stold multi Stold Measure: Na Dit Of Measure: Na Fig: Aziza0 Mil-stof(military Standard):	
First Step Length: Between 0.130 inches and 0.135 inches Second Step Diameter: Between 0.244 inches and 0.249 inches Second Step Length: 1.554 inches First End Taper Length: 0.063 inches First End Taper Angle: 45.0 degrees Pin Head Diameter: 1.000 inches Height: 0.003 inches Material: Stel comp 4130 Material Specification: Mil-s-6758, cond d military specification single material response Strike Treatment: Cadmium Shoulder Shoulder Pint Head Specification: Na Stel Comp 4130 Mil-s-6758, cond d military specification single material response Surface Treatment: Cadmium Shoulder Shoulder Shoulder Should Shoulder Should Sho	
Between 0.130 inches and 0.135 inches Second Step Diameter: Between 0.244 inches and 0.249 inches Second Step Length: 1.554 inches First End Taper Length: 0.063 inches First End Taper Angle: 45.0 degrees Pin Head Diameter: 1.000 inches Height: 0.063 inches Material: Steel comp 4130 Material Specification: Mil-s-6758, cond d military specification single material response Surface Treatment: Cadmium Style Designator: Shoulder Pinf Heasure: Na Stelf Life: N/a Unit Of Measure: - Demilitarization: No Fig: A212a0 Mil-s-td (military Standard):	
Second Step Diameter:Between 0.244 inches and 0.249 inchesSecond Step Length:1.554 inchesFirst End Taper Length:0.063 inchesFirst End Taper Angle:45.0 degreesPin Head Diameter:1.000 inchesHeight:0.063 inchesMaterial:Steel comp 4130Material Specification:Mil-s-6758, cond d military specification single material responseSurface Treatment:CadmiumShelf Life:N/aDinel Measure:NaDinel Measure:NaLife Measure:NaPinel Measure:NaPinel Measure:NaPinel Measure:Pinel Measure:NaPinel Measure:NaPinel Measure:Pinel Measure:NaPinel Measure:Pinel Measure:NaPinel Measure:Pinel Measur	
Between 0.244 inches and 0.249 inches Second Step Length: 1.554 inches First End Taper Length: 0.063 inches First End Taper Angle: 45.0 degrees Pin Head Diameter: 1.000 inches Height: 0.063 inches Material: Steel comp 4130 Material Specification: Mil-s-6758, cond d military specification single material response Surface Treatment: Cadmium Style Designator: Shoulder Material: Na Diff Measure: Na Style Designator: Shoulder Shell Life: Na Diff Measure: - Demilitarization: No Fig: A212a0 Mil-s-td (military Standard):	
Second Step Length: 1.554 inches 1.554 inches First End Taper Length: 0.063 inches First End Taper Angle: 45.0 degrees Pin Head Diameter: 1.000 inches Height: 0.063 inches Material: 0.063 inches Material: Steel comp 4130 Material Specification: Mil-s-6758, cond d military specification single material response Surface Treatment: Cadmium Style Designator: Shoulder Hife: Na Charl Massure: Demilitarization: No Fig: A212a0 Hil-st (military Standard):	
1.554 inches First End Taper Length: 0.063 inches First End Taper Angle: 45.0 degrees Pin Head Diameter: 1.000 inches Height: 0.063 inches Material: Steel comp 4130 Material Specification: Mil-s-6758, cond d military specification single material response Surface Treatment: Cadmium Style Designator: Shoulder Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig: A212a0 Mil-std (military Standard):	
First End Taper Length:0.063 inchesFirst End Taper Angle:45.0 degreesPin Head Diameter:1.000 inchesHeight:0.063 inchesMaterial:0.063 inchesMaterial Specification:Mil-s-6758, cond d military specification single material responseSurface Treatment:CadmiumShoulderShoulderShoulderCadmiumCadmiumShoulderShoulderShelf Life:N/aCation:ToPamilitarization:NaShelf Life:NaShelf Life:NaShelf Life:NaShelf Life:NaShelf Life:NaShelf Life:NaShelf Life:Shelf Life:NaShelf Life:NaShelf Life:Shelf Life: <td></td>	
0.063 inches First End Taper Angle: 45.0 degrees Pin Head Diameter: 1.000 inches Height: 0.063 inches Material: 0.063 inches Material: Steel comp 4130 Material Specification: Mil-s-6758, cond d military specification single material response Surface Treatment: Cadmium Style Designator: Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A212a0 Mil-ste (military Standard):	
First End Taper Angle:45.0 degreesPin Head Diameter:1.000 inchesHeight:0.063 inchesMaterial:Steel comp 4130Material Specification:Mil-s-6758, cond d military specification single material responseSurface Treatment:CadmiumShoulderShelf Life:N/aDit of Measure:Pemilitarization:NoFig:AlzaaHig:AlzaaKig:AlzaaMateriation:NoFig:AlzaaMateriation:AlzaaMateriation:KalzaaFig:AlzaaMateriation:AlzaaMateriation:AlzaaMateriation:M	
45.0 degrees Pin Head Diameter: 1.000 inches Height: 0.063 inches Material: Steel comp 4130 Material Specification: Mil-s-6758, cond d military specification single material response Surface Treatment: Cadmium Style Designator: Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A212a0	
Pin Head Diameter:1.000 inchesHeight:0.063 inchesMaterial:Steel comp 4130Material Specification:Mil-s-6758, cond d military specification single material responseSurface Treatment:CadmiumStyle Designator:ShoulderShelf Life:N/aUnit Of Measure:Penilitarization:NoFig:Az12a0Mil-s-td (military Standard):Mil-s-td (military Standard):	
1.000 inches Height: O.063 inches Material: Steel comp 4130 Material Specification: Mil-s-6758, cond d military specification single material response Surface Treatment: Cadmium Style Designator: Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A212a0 Mil-set (military Standard):	-
Height:0.063 inchesMaterial:Steel comp 4130Material Specification:Mil-s-6758, cond d military specification single material responseSurface Treatment:CadmiumStyle Designator:ShoulderShelf Life:N/aUnit Of Measure:-Pomilitarization:NoFig:A212a0Mil-set (military Standard):	
0.063 inches Material: Steel comp 4130 Material Specification: Mil-s-6758, cond d military specification single material response Surface Treatment: Cadmium Style Designator: Shoulder Shoulder Sheif Life: N/a Unit Of Measure: - Demilitarization: No Fig: A212a0	
Material:Steel comp 4130Material Specification:Mil-s-6758, cond d military specification single material responseSurface Treatment:CadmiumCadmiumStyle Designator:ShoulderSheif Life:N/aUnit Of Measure:Demilitarization:NoFig:A212a0Mil-set (military Standard):	
Steel comp 4130 Material Specification: Mil-s-6758, cond d military specification single material response Surface Treatment: Cadmium Style Designator: Shoulder Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A212a0 Mil-std (military Standard):	
Material Specification:Mil-s-6758, cond d military specification single material responseSurface Treatment:CadmiumCadmiumStyle Designator:ShoulderShelf Life:N/aUnit Of Measure:Demilitarization:NoFilg:A212a0Mil-setd (military Standard):	
Mil-s-6758, cond d military specification single material response Surface Treatment: Cadmium Style Designator: Shoulder Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A212a0 Mil-std (military Standard):	
Surface Treatment:CadmiumStyle Designator:ShoulderShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:A212a0Mil-std (military Standard):	-
Cadmium Style Designator: Shoulder Shoulder N/a Unit Of Measure: Demilitarization: No Fiig: A212a0 Mil-std (military Standard):	
Style Designator:ShoulderShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:A212a0Mil-std (military Standard):	
Shoulder Shoulder Shoulder Shoulder Shoulder Sholf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A212a0 Mil-std (military Standard):	
Shelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:A212a0Mil-std (military Standard):	
Unit Of Measure: Demilitarization: No Fiig: A212a0 Mil-std (military Standard):	
 Demilitarization: No Fiig: A212a0 Mil-std (military Standard):	N/a
No Fiig: A212a0 Mil-std (military Standard):	Unit Of Measure:
No Fiig: A212a0 Mil-std (military Standard):	
Fiig: A212a0 Mil-std (military Standard):	Demilitarization:
A212a0 Mil-std (military Standard):	No
Mil-std (military Standard):	Fiig:
	A212a0
Mil-s-6758 spec.	Mil-std (military Standard):
	Mil-s-6758 spec.