## NSN 5315-00-335-2014



Headless Shoulder Pin - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5315-00-335-2014 First End Style: Chamfered **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.234 inches **Shank Length:** 0.080 inches **Shoulder Width Across Flats:** 0.250 inches **Shank Diameter:** 0.124 inches **Overall Length:** 0.813 inches **Undercut Diameter:** 0.119 inches **Undercut Width:** 0.012 inches **Second Undercut Diameter:** 0.125 inches First End Taper Length: 0.010 inches Second End Relationship With First End: Identical **Hardness Rating:** 36.0 rockwell c and 42.0 rockwell c **Thread Size:** 0.164 inches **Second Shank Diameter:** 0.164 inches **First End Location:** Both ends First End Taper Angle: 45.0 degrees

Second Shank Length: 0.234 inches

Material:

Steel comp 416

**Material Specification:** 

Qq-s-764, cond a federal specification single material response

## NSN 5315-00-335-2014

Headless Shoulder Pin - Page 2 of 2

**Fiig:** A212a0



Surface Treatment:
Oxide
Test Data Document:
98230-ce11631 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No