

View Online at <https://aerobasegroup.com/nsn/5315-00-335-4710>

**First End Style:**

Chamfered

**Second End Style:**

Pointed

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.800 inches and 0.820 inches

**Shank Length:**

Between 1.050 inches and 1.070 inches

**Shoulder Width Across Flats:**

Between 0.490 inches and 0.510 inches

**Shank Diameter:**

Between 0.309 inches and 0.312 inches

**Overall Length:**

Between 5.300 inches and 5.320 inches

**Hole Arrangement Style:**

One end drilled

**First Hole Diameter:**

Between 0.068 inches and 0.088 inches

**Distance From Centerline Of Hole To End Of Pin:**

0.180 inches

**First End Taper Length:**

Between 0.180 inches and 0.200 inches

**Second End Taper Length:**

Any acceptable

**Second End Relationship With First End:**

Not identical

**Thread Size:**

0.312 inches

**Second Shank Diameter:**

Between 0.316 inches and 0.319 inches

**First End Location:**

Short shank end

**First End Taper Angle:**

60.0 degrees

**Second End Taper Angle:**

Any acceptable

**Second Shank Length:**

Between 2.550 inches and 2.570 inches

**Material:**

Steel comp 1010 or steel comp b1112

**Material Specification:**

Aisi assn standard 1st material response or aisi 1211 assn standard 2nd material response

**Style Designator:**

Shoulder

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0