# NSN 5315-00-338-1620

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-338-1620

### Head Diameter:

Between 0.640 inches and 0.755 inches

### Handle Length:

Between 2.125 inches and 2.250 inches

### Shank Diameter:

Between 0.4970 inches and 0.4985 inches

### **Detent Quantity:**

2

### **Actuation Method:**

Push button

**End Application:** 

W/s: torpedo, adcap 48

### Grip Length:

Between 1.000 inches and 1.020 inches

### Actuation Type:

Pull and push

## Hardness Rating:

40.0 rockwell c spindle

### Shoulder To Head End Distance:

1.270 inches

### Pin Attachment Type:

Link or ring

### **Detent To Tapered End Distance:**

0.590 inches

Material:

Steel comp 630 spindle or steel comp 632 spindle

### **Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

### Surface Treatment:

Passivate spindle

### Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

### Style Designator:

T handle

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A212a0