NSN 5315-00-341-9242

Threaded Tapered Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-341-9242

| First End Style: |
|---|
| Oval |
| Second End Style: |
| Oval |
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.620 inches |
| Taper Length: |
| 1.938 inches |
| Taper Minor Diameter: |
| 0.450 inches |
| Taper Major Diameter: |
| Between 0.476 inches and 0.479 inches |
| Grip Length: |
| 1.380 inches |
| Second End Relationship With First End: |
| Not identical |
| Thread Size: |
| 0.438 inches |
| Taper: |
| 0.0208 per foot in inches |
| First End Location: |
| Threaded end |
| Criticality Code Justification: |
| Abqb |
| First End Outer Radius: |
| Between 0.476 inches and 0.479 inches |
| Second End Outer Radius: |
| 0.450 inches |
| Material: |
| Steel comp 1010 or steel comp 1030 |
| Material Specification: |
| Fed standard 66 federal standard all material responses |
| Surface Treatment: |
| Phosphate manganese |
| Surface Treatment Specification: |
| Mil-p-16232 type m class 1 military specification single treatment response |
| Style Designator: |

Threaded at large end

NSN 5315-00-341-9242

Threaded Tapered Pin - Page 2 of 2



| Thread Series Designator: |
|------------------------------|
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A212a0 |
| Mil-std (military Standard): |

Mil-p-16232 spec.