

View Online at <https://aerobasegroup.com/nsn/5315-00-354-8859>

First End Style:

Chamfered

Overall Length:

Between 3.609 inches and 3.641 inches

Diameter:

Between 1.248 inches and 1.249 inches

Effective Length:

Between 2.172 inches and 2.203 inches

Undercut Diameter:

Between 1.172 inches and 1.203 inches

Undercut Width:

Between 0.109 inches and 0.141 inches

Second Undercut Width:

Between 0.109 inches and 0.141 inches

Hole Arrangement Style:

Both end drilled

First Hole Diameter:

Between 0.109 inches and 0.141 inches

Second Hole Diameter:

Between 0.109 inches and 0.141 inches

Distance From Centerline Of Hole To End Of Pin:

0.656 inches

Center To Center Distance Between Holes:

Between 2.297 inches and 2.328 inches

First End Taper Length:

Between 0.047 inches and 0.078 inches

Features Provided:

Casehardened

Second End Relationship With First End:

Identical

Hardness Rating:

56.0 rockwell c and 62.0 rockwell c

First End Location:

Both ends

First End Taper Angle:

Between 44.0 degrees and 46.0 degrees

Surface Finish:

63.0 microinches shank end

Special Features:

One slot in middle of effective lg 0.266 to 0.297 in. Width

Material:

Steel comp 1025 or steel comp 1020

Material Specification:

Aisi assn standard all material responses

Style Designator:

Groove

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0