NSN 5315-00-363-8100

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-363-8100 First End Style: Chamfered **Shank Length:** 0.359 inches **Shoulder Diameter:** Between 0.304 inches and 0.309 inches **Shank Diameter:** Between 0.245 inches and 0.251 inches **Overall Length:** 0.938 inches **Undercut Diameter:** Between 0.216 inches and 0.222 inches **Undercut Width:** Between 0.050 inches and 0.055 inches **Second Undercut Width:** Any acceptable **Second Undercut Diameter:** Any acceptable First End Taper Length: 0.031 inches **Features Provided:** Casehardened **Second End Relationship With First End:** Identical Hardness Rating: 78.0 rockwell a and 83.0 rockwell a **Second Shank Diameter:** Between 0.245 inches and 0.251 inches **First End Location:** Both ends First End Taper Angle: 30.0 degrees **Second Shank Length:** 0.359 inches **Special Features:** Undercut located 0.047 in. From shoulder end Material: Steel **Style Designator:**

Undercut Shelf Life: N/a

NSN 5315-00-363-8100

Headless Shoulder Pin - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A212a0