## NSN 5315-00-364-1751

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-364-1751

| First End Style:   |
|--|
| Chamfered  |
| Shank Length:  |
| 0.125 inches   |
| Shoulder Diameter:   |
| 0.625 inches   |
| Shank Diameter:  |
| Between 0.498 inches and 0.499 inches                                  |
| Overall Length:  |
| 0.641 inches   |
| Undercut Diameter:   |
| 0.469 inches   |
| Undercut Width:  |
| 0.031 inches   |
| Second Undercut Width:   |
| 0.031 inches   |
| First End Taper Length:  |
| 0.016 inches   |
| Second End Relationship With First End:                                |
| Identical  |
| Hardness Rating:   |
| 28.0 rockwell c and 32.0 rockwell c                                    |
| Second Shank Diameter:   |
| Between 0.5005 inches and 0.5015 inches                                |
| First End Location:  |
| Both ends  |
| First End Taper Angle:   |
| 45.0 degrees   |
| Second Shank Length:   |
| 0.281 inches   |
| Material:  |
| Steel  |
| Material Specification:  |
| Mil-s-890, alloy no. 3 military specification single material response |
| Style Designator:  |
| Undercut   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
|  |
|  |

## NSN 5315-00-364-1751

Headless Shoulder Pin - Page 2 of 2

**Fiig:** A212a0

Mil-std (military Standard):

Mil-s-890 spec.

