

View Online at <https://aerobasegroup.com/nsn/5315-00-367-3913>

**Head Style:**

Flat chamfer

**Overall Length:**

1.975 inches

**Offset Distance Between Geometric Center Of Head And Centerline Of Shank/shoulder:**

0.100 inches

**Relief Under Head Diameter:**

0.200 inches

**Relief Under Head Length:**

0.060 inches

**First Step Diameter:**

Between 0.350 inches and 0.354 inches

**First Step Length:**

Between 0.420 inches and 0.480 inches

**Second Step Diameter:**

Between 0.3123 inches and 0.3126 inches

**Second Step Length:**

0.460 inches

**Third Step Diameter:**

Between 0.261 inches and 0.262 inches

**Third Step Length:**

0.275 inches

**Numeric Designation Of Step Eccentric To Head:**

3

**Features Provided:**

Casehardened

**Hardness Rating:**

58.0 rockwell c

**Pin Head Diameter:**

Between 0.248 inches and 0.249 inches

**Surface Finish:**

32.0 microinches undercut

**Height:**

0.230 inches

**Material:**

Steel comp 4620

**Material Specification:**

Mil-s-7493 military specification single material response

**Style Designator:**

Eccentric

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-7493 spec.