

View Online at <https://aerobasegroup.com/nsn/5315-00-384-2700>

**First End Style:**

Chamfered

**Head Style:**

Flat

**Diameter:**

Between 0.2491 inches and 0.2496 inches

**Effective Length:**

Between 1.595 inches and 1.610 inches

**Undercut Diameter:**

Between 0.230 inches and 0.240 inches

**Under Head Length:**

1.750 inches

**Undercut Width:**

Between 0.030 inches and 0.040 inches

**Hole Arrangement Style:**

One end drilled

**First Hole Diameter:**

Between 0.070 inches and 0.074 inches

**Distance From Centerline Of Hole To End Of Pin:**

0.120 inches

**First End Taper Length:**

Between 0.020 inches and 0.040 inches

**Grip Length:**

Between 1.630 inches and 1.645 inches

**First End Taper Angle:**

Between 44.5 degrees and 45.5 degrees

**Pin Head Diameter:**

0.375 inches

**Surface Finish:**

32.0 microinches shank end

**Height:**

Between 0.057 inches and 0.067 inches

**Material:**

Steel

**Material Specification:**

Mil-s-16782, cl 2, 3, or 4 military specification single material response or mil-s-16788, cl b or bs military specification single material response or mil-s-890 military specification single material response

**Style Designator:**

Groove

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-16782 spec.