

View Online at <https://aerobasegroup.com/nsn/5315-00-394-4169>

**Shank Diameter:**

Between 0.4970 inches and 0.4985 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**End Application:**

W/s: support equipment, h-3 helicopter; support equipment, b-52 aircraft; aircraft, f-111; engine, aircraft, f100-pw-100 (f-15a/b/c/d); support equipment, f-15 aircraft; support equipment, a-10 aircraft; support equipment, f-4 aircraft; aircraft, f-16; aircraft, eagle f-15

**Grip Length:**

Between 3.200 inches and 3.220 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c spindle

**Shoulder To Head End Distance:**

1.600 inches

**Pin Center To Handle End Distance:**

Between 1.730 inches and 1.860 inches

**Pin Attachment Type:**

Hook or ring

**Detent To Tapered End Distance:**

0.460 inches

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

L handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0