

View Online at <https://aerobasegroup.com/nsn/5315-00-394-4169>

Shank Diameter:

Between 0.4970 inches and 0.4985 inches

Detent Quantity:

2

Actuation Method:

Push button

End Application:

W/s: support equipment, h-3 helicopter; support equipment, b-52 aircraft; aircraft, f-111; engine, aircraft, f100-pw-100 (f-15a/b/c/d); support equipment, f-15 aircraft; support equipment, a-10 aircraft; support equipment, f-4 aircraft; aircraft, f-16; aircraft, eagle f-15

Grip Length:

Between 3.200 inches and 3.220 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c spindle

Shoulder To Head End Distance:

1.600 inches

Pin Center To Handle End Distance:

Between 1.730 inches and 1.860 inches

Pin Attachment Type:

Hook or ring

Detent To Tapered End Distance:

0.460 inches

Material:

Steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

Style Designator:

L handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0