NSN 5315-00-394-5259

Headless Shoulder Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-394-5259

Chamfered Shank Length: Between 0.371 inches and 0.375 inches Shoulder Diameter: 0.250 inches Shank Diameter: Between 0.1557 inches and 0.1561 inches Overall Length: 0.840 inches First End Taper Length: 0.020 inches Second End Relationship With First End: 1dentical Hardness Rating: 53.0 rockwell c and 60.0 rockwell c Second Shank Diameter: 0.1718 inches First End Location: Both ends First End Taper Angle: 45.0 degrees Surface Finish:
Between 0.371 inches and 0.375 inches Shoulder Diameter: 0.250 inches Shank Diameter: Between 0.1557 inches and 0.1561 inches Overall Length: 0.840 inches First End Taper Length: 0.020 inches Second End Relationship With First End: Identical Hardness Rating: 53.0 rockwell c_and 60.0 rockwell c Second Shank Diameter: 0.1718 inches First End Location: Both ends First End Taper Angle: 45.0 degrees
Shoulder Diameter: 0.250 inches Shank Diameter: Between 0.1557 inches and 0.1561 inches Overall Length: 0.840 inches First End Taper Length: 0.020 inches Second End Relationship With First End: Identical Hardness Rating: 53.0 rockwell c and 60.0 rockwell c Second Shank Diameter: 0.1718 inches First End Location: Both ends First End Taper Angle: 45.0 degrees
0.250 inches Shank Diameter: Between 0.1557 inches and 0.1561 inches Overall Length: 0.840 inches First End Taper Length: 0.020 inches Second End Relationship With First End: Identical Hardness Rating: 53.0 rockwell c and 60.0 rockwell c Second Shank Diameter: 0.1718 inches First End Location: Both ends First End Taper Angle: 45.0 degrees
Shank Diameter: Between 0.1557 inches and 0.1561 inches Overall Length: 0.840 inches First End Taper Length: 0.020 inches Second End Relationship With First End: Identical Hardness Rating: 53.0 rockwell c_and 60.0 rockwell c Second Shank Diameter: 0.1718 inches First End Location: Both ends First End Taper Angle: 45.0 degrees
Between 0.1557 inches and 0.1561 inches Overall Length: 0.840 inches First End Taper Length: 0.020 inches Second End Relationship With First End: Identical Hardness Rating: 53.0 rockwell c and 60.0 rockwell c Second Shank Diameter: 0.1718 inches First End Location: Both ends First End Taper Angle: 45.0 degrees
Overall Length: 0.840 inches First End Taper Length: 0.020 inches Second End Relationship With First End: Identical Hardness Rating: 53.0 rockwell c and 60.0 rockwell c Second Shank Diameter: 0.1718 inches First End Location: Both ends First End Taper Angle: 45.0 degrees
0.840 inches First End Taper Length: 0.020 inches Second End Relationship With First End: Identical Hardness Rating: 53.0 rockwell c and 60.0 rockwell c Second Shank Diameter: 0.1718 inches First End Location: Both ends First End Taper Angle: 45.0 degrees
First End Taper Length:0.020 inchesSecond End Relationship With First End:IdenticalHardness Rating:53.0 rockwell c and 60.0 rockwell cSecond Shank Diameter:0.1718 inchesFirst End Location:Both endsFirst End Taper Angle:45.0 degrees
0.020 inches Second End Relationship With First End: Identical Hardness Rating: 53.0 rockwell c and 60.0 rockwell c Second Shank Diameter: 0.1718 inches First End Location: Both ends First End Taper Angle: 45.0 degrees
Second End Relationship With First End: Identical Hardness Rating: 53.0 rockwell c and 60.0 rockwell c Second Shank Diameter: 0.1718 inches First End Location: Both ends First End Taper Angle: 45.0 degrees
Identical Hardness Rating: 53.0 rockwell c and 60.0 rockwell c Second Shank Diameter: 0.1718 inches First End Location: Both ends First End Taper Angle: 45.0 degrees
Hardness Rating: 53.0 rockwell c and 60.0 rockwell c Second Shank Diameter: 0.1718 inches First End Location: Both ends First End Taper Angle: 45.0 degrees
53.0 rockwell c and 60.0 rockwell c Second Shank Diameter: 0.1718 inches First End Location: Both ends First End Taper Angle: 45.0 degrees
Second Shank Diameter: 0.1718 inches First End Location: Both ends First End Taper Angle: 45.0 degrees
0.1718 inches First End Location: Both ends First End Taper Angle: 45.0 degrees
First End Location: Both ends First End Taper Angle: 45.0 degrees
Both ends First End Taper Angle: 45.0 degrees
First End Taper Angle: 45.0 degrees
45.0 degrees
-
Surface Finish:
63.0 microinches shank end
Second Shank Length:
0.430 inches
Material:
Steel comp 440c
Material Specification:
Ams5630 assn standard single material response
Surface Treatment:
Passivate
Style Designator:
Shoulder
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A212a0