## NSN 5315-00-395-1991

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-395-1991 First End Style: Chamfered Second End Style: Pointed **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.178 inches **Shank Length:** Between 0.990 inches and 1.000 inches **Shoulder Width Across Flats:** Between 0.362 inches and 0.375 inches **Shank Diameter:** Between 0.1866 inches and 0.1870 inches **Overall Length:** 1.300 inches First End Taper Length: Between 0.010 inches and 0.020 inches **Second End Taper Length:** 0.500 inches Second End Relationship With First End: Not identical **Thread Size:** 0.190 inches **Second Shank Diameter:** 0.190 inches **First End Location:** Threaded end First End Taper Angle: 45.0 degrees **Criticality Code Justification:** Aaze **Second Shank Length:** 0.240 inches **Special Features:** Pointed end has 0.030 in. Radius Material: Steel comp 630 **Material Specification:** Ams 5643 assn standard single material response

## NSN 5315-00-395-1991

Headless Shoulder Pin - Page 2 of 2



Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Style Designator:
Shoulder
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A212a0