

View Online at <https://aerobasegroup.com/nsn/5315-00-400-3512>

First End Style:

Square

Head Style:

Flat

Under Head Length:

Between 0.320 inches and 0.335 inches

First Step Diameter:

Between 0.2498 inches and 0.2500 inches

First Step Length:

Between 0.190 inches and 0.195 inches

Second Step Diameter:

Between 0.1246 inches and 0.1248 inches

Second Step Length:

Between 0.130 inches and 0.140 inches

Hardness Rating:

23.0 rockwell c and 32.0 rockwell c

Pin Head Diameter:

Between 0.620 inches and 0.640 inches

Criticality Code Justification:

Csym

Surface Finish:

63.0 microinches outside diameter

Special Features:

Three holes 0.115 csk 81 degrees x 0.165 in. Diameter equally spaced in top of head

Height:

Between 0.062 inches and 0.067 inches

Material:

Steel comp 416

Material Specification:

Qq-s-763 federal specification single material response

Surface Treatment:

Passivate and oxide

Surface Treatment Specification:

Mil-std-171 5.4.1 military standard 1st treatment response and mil-c-13924 class 4 military specification 2nd treatment response

Style Designator:

Shoulder

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-std-171 spec.