

View Online at <https://aerobasegroup.com/nsn/5315-00-404-8246>

Shank Diameter:

Between 0.3095 inches and 0.3110 inches

Detent Quantity:

2

Actuation Method:

Push button

End Application:

Wsd: missile, minuteman lgm-30; missile, all-weather anti-ship, harpoon (agm-84); agm-84e standoff land attack missile (slam)

Grip Length:

Between 2.200 inches and 2.220 inches

Actuation Type:

Push

Features Provided:

Lock open feature

Hardness Rating:

40.0 rockwell c spindle

Shoulder To Head End Distance:

1.270 inches

Criticality Code Justification:

Feat

Pin Center To Handle End Distance:

Between 1.380 inches and 1.460 inches

Pin Attachment Type:

Hook or ring

Detent To Tapered End Distance:

Between 0.300 inches and 0.330 inches

Special Features:

Weapon system essential

Material:

Steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

Style Designator:

L handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0