

View Online at <https://aerobasegroup.com/nsn/5315-00-404-8246>

**Shank Diameter:**

Between 0.3095 inches and 0.3110 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**End Application:**

Wsd: missile, minuteman lgm-30; missile, all-weather anti-ship, harpoon (agm-84); agm-84e standoff land attack missile (slam)

**Grip Length:**

Between 2.200 inches and 2.220 inches

**Actuation Type:**

Push

**Features Provided:**

Lock open feature

**Hardness Rating:**

40.0 rockwell c spindle

**Shoulder To Head End Distance:**

1.270 inches

**Criticality Code Justification:**

Feat

**Pin Center To Handle End Distance:**

Between 1.380 inches and 1.460 inches

**Pin Attachment Type:**

Hook or ring

**Detent To Tapered End Distance:**

Between 0.300 inches and 0.330 inches

**Special Features:**

Weapon system essential

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

L handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0