# NSN 5315-00-407-3456

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-407-3456

# Head Diameter:

Between 0.640 inches and 0.755 inches

# Shank Diameter:

Between 0.4970 inches and 0.4985 inches

# **Ring Handle Diameter:**

Between 1.000 inches and 1.125 inches

# **Detent Quantity:**

2

### **Actuation Method:**

Push button

Grip Length:

Between 2.000 inches and 2.020 inches

### Actuation Type:

Pull and push

#### Hardness Rating:

40.0 rockwell c spindle

# Shoulder To Head End Distance:

1.070 inches

# Pin Attachment Type:

Hook

# Detent To Tapered End Distance:

Between 0.540 inches and 0.590 inches

Material:

Steel comp 630 spindle or steel comp 632 spindle

# **Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

# Surface Treatment:

Passivate spindle

# Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

# Style Designator:

Ring handle

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A212a0