NSN 5315-00-410-3442

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-410-3442

First End Style:
Chamfered
Shank Length:
1.813 inches
Shoulder Diameter:
Between 1.528 inches and 1.530 inches
Shank Diameter:
Between 1.030 inches and 1.060 inches
Overall Length:
Between 7.770 inches and 7.810 inches
Undercut Diameter:
Between 0.860 inches and 0.880 inches
Undercut Width:
0.312 inches
Hole Arrangement Style:
One end drilled
First Hole Diameter:
Between 0.344 inches and 0.351 inches
Distance From Centerline Of Hole To End Of Pin:
3.630 inches
First End Taper Length:
Between 0.040 inches and 0.060 inches
Features Provided:
Casehardened
Second End Relationship With First End:
Identical
Second Shank Diameter:
Between 0.997 inches and 0.999 inches
First End Location:
Both ends
Surface Finish:
63.0 microinches outside diameter
Second Shank Length:
Between 1.370 inches and 1.390 inches
Special Features:
Long shank has medium diamond knurl; shoulder end opposite groove chamfered 30 deg
Material:
Steel
Material Specification:
Aisi 8620 assn standard single material response
Style Designator:
Undercut

NSN 5315-00-410-3442

Headless Shoulder Pin - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0