

View Online at <https://aerobasegroup.com/nsn/5315-00-413-1339>

**First End Style:**

Chamfered

**Second End Style:**

Pointed

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.438 inches

**Shank Length:**

0.562 inches

**Shoulder Width Across Flats:**

0.625 inches

**Shank Diameter:**

Between 0.308 inches and 0.309 inches

**Overall Length:**

1.400 inches

**First End Taper Length:**

0.031 inches

**Second End Taper Length:**

0.031 inches

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

35.0 rockwell c and 43.0 rockwell c

**Thread Size:**

0.312 inches

**Second Shank Diameter:**

0.312 inches

**First End Location:**

Threaded end

**First End Taper Angle:**

60.0 degrees

**Surface Finish:**

125.000 microinches

**Second End Taper Angle:**

60.0 degrees

**Second Shank Length:**

0.562 inches

**Material:**

Steel comp 630

**Material Specification:**

Ams 5643 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response

**Style Designator:**

Shoulder

**Test Data Document:**

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-s-5002 spec.