# NSN 5315-00-417-8559

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-417-8559

## Head Diameter:

Between 0.360 inches and 0.450 inches

## Shank Diameter:

Between 0.2470 inches and 0.2485 inches

## Ring Handle Diameter:

Between 1.000 inches and 1.125 inches

## **Detent Quantity:**

2

#### **Actuation Method:**

Push button

Grip Length:

Between 1.700 inches and 1.720 inches

## Actuation Type:

Pull and push

#### Hardness Rating:

36.0 rockwell c spindle and 40.0 rockwell c spindle

#### Shear Strength:

8200 double pounds per square inch

## Shoulder To Head End Distance:

0.935 inches

# Pin Attachment Type:

Hook

# Detent To Tapered End Distance:

Between 0.360 inches and 0.410 inches

# **Special Features:**

Steel attaching hook or ring, spec qq-w-428, type 1

#### Material:

Steel spring

# **Material Specification:**

Qq-w-470 federal specification single material response spring

#### Surface Treatment:

Passivate ring

# Surface Treatment Specification:

Qq-p-35 federal specification single treatment response ring

#### Style Designator:

Ring handle

Shelf Life:

N/a

Unit Of Measure:

--

## Demilitarization:

No

# NSN 5315-00-417-8559

Quick Release Pin - Page 2 of 2

Fiig: A212a0 Mil-std (military Standard): Mil-s-6758 spec.

