## NSN 5315-00-419-0741

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-419-0741

First End Style: Chamfered Second End Style: Chamfered **Thread Class:** 2a **Thread Direction: Right-hand Thread Length:** 0.540 inches Shank Length: 0.620 inches **Shoulder Diameter:** 0.625 inches **Shoulder Width Across Flats:** 0.500 inches Shank Diameter: Between 0.244 inches and 0.246 inches **Overall Length:** 1.660 inches First End Taper Length: 0.030 inches Second End Taper Length: 0.250 inches Second End Relationship With First End:

Not identical

Hardness Rating:

40.0 rockwell c and 43.0 rockwell c

Thread Size:

0.250 inches

Second Shank Diameter:

Between 0.247 inches and 0.249 inches

**First End Location:** 

Threaded end

First End Taper Angle:

45.0 degrees

Surface Finish:

63.000 microinches both ends

Second End Taper Angle:

30.0 degrees

Second Shank Length:

0.790 inches

## NSN 5315-00-419-0741

Headless Shoulder Pin - Page 2 of 2



Material:

Steel comp 416

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-14072, e300 military specification single treatment response

Style Designator:

Shoulder

**Thread Series Designator:** 

Unf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-f-14072 spec.