## NSN 5315-00-420-0271

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-420-0271 First End Style: Chamfered Second End Style: Chamfered **Thread Class:** 2a **Thread Pitch Diameters:** +0.2810/+0.2825 inches **Thread Direction:** Right-hand Thread Length: 0.312 inches **Shank Length:** 0.562 inches **Shoulder Width Across Flats:** 0.497 inches **Shank Diameter:** 0.307 inches **Overall Length:** 1.375 inches First End Taper Length: 0.045 inches **Second End Taper Length:** 0.060 inches Second End Relationship With First End: Not identical Hardness Rating: 26.0 rockwell c and 32.0 rockwell c **Thread Size:** 0.312 inches **Second Shank Diameter:** 0.307 inches **First End Location:** Both ends First End Taper Angle: 20.0 degrees **Surface Finish:** 63.000 microinches **Second End Taper Angle:** 

45.0 degrees **Second Shank Length:** 

0.625 inches

## NSN 5315-00-420-0271

Headless Shoulder Pin - Page 2 of 2



Material:
Steel
Surface Treatment:
Cadmium
Surface Treatment Specification:
Ams 2400 assn standard single treatment response
Style Designator:
Shoulder
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A212a0