## NSN 5315-00-421-7850



Quick Release Pin - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5315-00-421-7850 **Shank Diameter:** Between 0.3095 inches and 0.3110 inches **Button Handle Diameter:** Between 0.810 inches and 1.135 inches **Detent Quantity: Actuation Method:** Push button **End Application:** W/s: missile, air-to-air, sparrow (aim-7); aircraft, airlifter c-17a **Grip Length:** Between 0.300 inches and 0.320 inches **Actuation Type:** Push **Hardness Rating:** 40.0 rockwell c spindle **Shoulder To Head End Distance:** 0.930 inches Pin Attachment Type: Hook or ring **Detent To Tapered End Distance:** Between 0.300 inches and 0.330 inches Material: Steel comp 630 spindle or steel comp 632 spindle **Material Specification:** Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle **Surface Treatment:** Passivate spindle **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response spindle **Style Designator: Button** 

Qq-p-35 federal specification single treatment response spindle

Style Designator:

Button

Shelf Life:

N/a

Unit Of Measure:

-
Demilitarization:

No

Fiig:

A212a0